



**TACTICAL
COMMAND
INDUSTRIES, INC.**

EAST COAST DIVISION:
P.O. Box 70
Gilmanton, NH 03237
(603) 418-8705 tel.
(866) 255-9414 fax

**MIDWEST SALES
DIVISION:**
(317) 861-1740 tel.
(866) 255-9414 fax

WEST COAST DIVISION:
2101 West 10th Street
Bldg. G
Antioch, CA 94509
(925) 219-1097 tel.
(925) 756-7977 fax

TACTICALCOMMAND.COM

**TACTICAL
COMMAND**

© TCI INC. 2011

TCI DEHP PRO-X DIGITAL ELECTRONIC HEARING PROTECTION



TCI DEHP PRO-X DIGITAL ELECTRONIC HEARING PROTECTION > DEHP PRO X

Durable, high-performance electronic hearing protection is critical when exposed to sound levels exceeding 85 dB, but many hearing protection products are inferior in various ways.

TCI's electronic hearing protection was designed to exceed the performance of other hearing protectors and does so in the following categories:

- **Protection, Sound Attenuation and Situational Awareness**
- **Durability**
- **Battery Life**
- **Comfort**

Specific Performance Attributes Include:

- Digital Sound Processing Provides Superb Hearing Protection using State of the Art Threat Compression Technology.
- BTH Behind-the-Head (above-left) or OTH Over-the-Head Suspension (above-right) Options Available.
- Available with OD Green or Black Color Earcups.
- Low-Profile Earcup Design.
- Two Separate, Well-Shielded Microphones for Exceptional Situational Awareness and Localization of Ambient Sounds.
- Four Volume Settings Provide Amplification of Distant Sounds as well as Accurate Replication of Ambient Sounds.
- 600 Hours Battery Life—Uses Two Standard AAA Batteries. Single Waterproof Battery Compartment.
- Volume Memory, Auto-Shut-Off, and Low-Power Warning.
- Exceptional Environmental Protection Against the Effects of Water, Humidity, Dust, Temperature, plus RF and EMI Protection.
- Robust MIL-SPEC Durability.
- 3.5 MM Aux Audio Input Jack for Certain Consumer Applications
- Gel Ear-Seal Upgrade **Included**
- Weight: 9.9 Ounces.

TCI OEM HEARING PROTECTION: ATTENUATION CHART							
EN352-1/EN352-4/EN352-6: SNR = 24 dB, H = 26 dB, M = 21 dB, L = 15 dB							
Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Value (dB)	11.0	16.0	23.0	24.6	27.4	38.8	41.1
Std. Dev. (dB)	3.9	2.1	2.0	3.1	3.1	38.	3.7
APV Value (dB)	7.1	13.9	21.0	21.6	24.3	34.9	37.3
ANSI S3.19-1974:	NNR = 21 dB						

LEADERS IN COMBAT COMMUNICATIONS